


# PS

## 관용 평행 나사



품구: 1G



규격	재고	상품코드	식부 Chamfer	등급	외경의 기준치수 (mm)	$L$ (mm)	$l$ (mm)	$D_s$ (mm)	$K$ (mm)	$l_k$ (mm)	흡수	형상
<b>관용</b>												
1/16-28	△	TH2P01K-8	3.5P	II	7.723	55	19	8	6	9	4	v
1/8-28	◎	TH2P02K	3.5P	II	9.728	55	19	8	6	9	4	v
	△	TH2P02K1	1.5P									
1/4-19	◎	TH2P04-	3.5P	II	13.157	62	28	11	9	12	4	v
	△	TH2P04-1	1.5P									
3/8-19	◎	TH2P06-	3.5P	II	16.662	65	28	14	11	14	4	v
	△	TH2P06-1	1.5P									
1/2-14	◎	TH2P08Q	3.5P	II	20.955	80	35	18	14	17	4	v
	△	TH2P08Q1	1.5P									
5/8-14	△	TH2P10Q	3.5P	II	22.911	82	35	19	15	18	4	v
3/4-14	◎	TH2P12Q	3.5P	II	26.441	85	35	23	17	20	4	v
	△	TH2P12Q1	1.5P									
7/8-14	△	TH2P14Q	3.5P	II	30.201	90	40	24	19	22	4	v
1'-11	◎	TH2P16U	3.5P	II	33.249	95	45	26	21	24	5	v

규격	재고	상품코드	식부 Chamfer	등급	외경의 기준치수 (mm)	$L$ (mm)	$l$ (mm)	$D_s$ (mm)	$K$ (mm)	$l_k$ (mm)	흡수	형상
1'-11	△	TH2P16U1	1.5P	II	33.249	95	45	26	21	24	5	v
1'1/4-11	○	TH2P20U	3.5P	II	41.910	105	45	32	26	30	5	v
	△	TH2P20U1	1.5P									
1'1/2-11	○	TH2P24U	3.5P	II	47.803	110	45	38	29	32	6	v
	△	TH2P24U1	1.5P									
2'-11	○	TH2P32U	3.5P	II	59.614	120	50	46	35	38	6	v
2'1/2-11	△	TH2P40U	3.5P	II	75.184	145	65	55	41	44	8	v
3'-11	△	TH2P48U	3.5P	II	87.844	155	65	65	50	52	8	v
4'-11	△	TH2P64U	3.5P	II	113.030	170	70	75	58	62	10	v